



MOBILE ▶ STATIC ▶ DIESEL POWER ▶ ELECTRIC



Transport by flat trailer or hook loader roll on roll off



Transport position to working position is less than 20 minutes, no conveyor belts to open



Easy drum exchange with other 518 drums







## ◀ ◀ GO SCREEN GO SORT ▶ ▶



Easy access to power unit, hopper sliding out



simple and efficient control unit



Large rear wheels to move around yard  
Material discharge on both sides of machine

## XD518H

- ▶ Self erecting machine to working position with hydraulically adjustable jacking legs via remote control
- ▶ Bay under trommel with side walls creating storage volume approximately 22m<sup>3</sup>, non heaped
- ▶ Drum load sensing system
- ▶ Engine protection system
- ▶ Caterpillar diesel engine C 2.2, 38 kW (51hp)
- ▶ Hopper capacity 4.5m<sup>3</sup> heaped
- ▶ Hydraulically removable hopper sliding horizontal for quick drum change
- ▶ Variable drum speed with reverse function
- ▶ Variable hopper belt speed with reverse function
- ▶ Hydraulically foldable cleaning brush with individual brush elements and cleaners
- ▶ Permissible total weight approx 8,100kg

**Kentek**  
SYSTEMS

For more information please contact:  
Gerard Mc Fadden  
Mobile: +353 (0)87 2494908